Data Sheet

LB 1010 INT - 08.2026 -0025

MeiStream

Bulk meter for cold potable water DN 40 ... 300

Main characteristics

- Meter with MID pattern approval acc. to annex MI001
- Exchangeable metrological unit with MID pattern approval acc. to annex MI001
- Unique measuring range; $Q_3/Q_1 \geq 100$
- High overload capability
- No straight inlet length necessary (U0D0 acc. to OIML R49:2013 and ISO 4064-1:2017)
- Installation position horizontal and vertical
- Meter body in short (WP) and long (WS) overall length acc. to DIN 19625 and ISO 4064-1:2017 available
- Meter can be submerged; protection class IP68
- Used materials are temperature resistant up to 70 °C
- Register prepared for HRI-Mei pick-up
- Use of optical pulsers type OD is still possible



Applications

- Measurement for billing of cold potable water up to 50 °C
- Measurement of high flowrates e.g. in pumped pipes
- Measurement of low flow e. g. in light load periods
- For leakage detection

INDORAYA POWER ENERGI

Available options

- Encoder register with different data protocols (M-Bus, Sensus, IEC 1107)
- BMF version free of copper alloy for aggressive water (DN 40 ...150)
- Register with 7 digits without multiplier (DN 150 ... 300)
- Version for high pressure up to PN 40 (DN 50 ... 150)
- Version for use in hazardous area
- HRI-Mei factory mounted
- ¼" pressure monitoring port

Environmental conditions

- According to ISO 4064-1:2017
- Environmental class O acc. to OIML R49-1:2013
- Environmental temperature: 5 °C ... 70 °C
- Mechanical environmental conditions: class M2

Metrological data acc. to manufacturers values

	Size		DN 40	DN 50	DN 65	DN 80	DN 100
Q_S	Max. Peak Flow	m³/h	60	90	120	200	300
Q_3'	Continuous Flow	m³/h	40	50	70	120	230
Q_{2h}	Transitional Flowrate horizontal	m³/h	0.32	0.4	0.63	0.51	0.81
Q_{1h}'	Minimum Flow horizontal	m³/h	0.2	0.15	0.2	0.2	0.3
Q_{2v}	Transitional Flowrate vertical	m³/h	0.4	0.51	0.81	0.8	1.28
Q_{1v}'	Minimum Flow vertical	m³/h	0.25	0.28	0.4	0.5	0.5
	Starting Flow	m³/h	0.05	0.05	0.07	0.1	0.11

	Size		DN 125	DN 150	DN 200	DN 250	DN 300
Q_S	Max. Peak Flow	m³/h	350	600	1200	1600	2000
Q_3'	Continuous Flow	m³/h	250	450	800	1250	1400
Q_{2h}	Transitional Flowrate horizontal	m³/h	1.02	1.6	4.0	6.3	16.0
Q_{1h}'	Minimum Flow horizontal	m³/h	0.5	0.8	2.0	3.5	9.0
Q_{2v}	Transitional Flowrate vertical	m³/h	1.6	3.2	4.0	10.1	25.4
Q_{1v}'	Minimum Flow vertical	m³/h	1	1.6	2.5	6.3	15.9
	Starting Flow	m³/h	0.15	0.3	1.5	3	8


Metrological data acc. to 2014/32/EU (MID)

	Size		DN 40	DN 50	DN 65	DN 80	DN 100
Q_4	Overload Flowrate acc. to MID	m³/h	31.25	50	78.75	125	200
Q_3	Permanent Flowrate acc. to MID	m³/h	25	40	63	100	160
Q_{2h}	Transitional Flowrate horizontal acc. to MID	m³/h	0.32	0.4	0.63	0.51	0.81
Q_{1h}	Minimum Flowrate horizontal acc. to MID	m³/h	0.2	0.25	0.39	0.32	0.51
Q_{2v}	Transitional Flowrate vertical acc. to MID	m³/h	0.635	0.64	1.0	1.28	1.6
Q_{1v}	Minimum Flowrate vertical acc. to MID	m³/h	0.4	0.4	0.63	0.8	1.0
Q_3/Q_1 h	Max. Ratio horizontal		125	160	160	315	315
Q_3/Q_1 v	Max. Ratio vertical		63	100	100	125	160
Q_3/Q_1	Standard Marking		63	100	100	100	100
Δp	Headloss at Q_3 acc. to ISO 4064-1:2017	bar	0.1	0.16	0.32	0.16	0.34


	Size		DN 125	DN 150	DN 200	DN 250	DN 300
Q_4	Overload Flowrate acc. to MID	m³/h	200	500	787.5	787.5	1250
Q_3	Permanent Flowrate acc. to MID	m³/h	160	400	630	630	1000
Q_{2h}	Transitional Flowrate horizontal acc. to MID	m³/h	1.02	1.6	4.03	8.06	25.4
Q_{1h}	Minimum Flowrate horizontal acc. to MID	m³/h	0.64	1	2.52	5.04	15.9
Q_{2v}	Transitional Flowrate vertical acc. to MID	m³/h	2.05	3.2	4.03	10.1	25.4
Q_{1v}	Minimum Flowrate vertical acc. to MID	m³/h	1.28	2	2.52	6.3	15.9
Q_3/Q_1 h	Max. Ratio horizontal		250	400	250	125	63
Q_3/Q_1 v	Max. Ratio vertical		125	200	250	100	63
Q_3/Q_1	Standard Marking		100	100	100	100	63
Δp	Headloss at Q_3 acc. to ISO 4064-1:2017	bar	0.19	0.27	0.11	0.07	0.08

INDORAYA POWER ENERGI

Dial




DN 40...125



DN 150 ... 300

Typical Error Curve




Pulse values

Pulse type	Pulse Value DN 40 ... 125	Pulse Value DN 150 ... 300
HRI-Mei	0.01; 0.05; 0.1 or 1 m³	0.1; 0.5; 1 or 10 m³
OD 01	0.001 m³	0.01 m³
OD 03	0.01 m³	0.1 m³

Reading

Nominal diameter	Smallest reading	Maximum reading
DN 40 ... 125	0.0005 m³	999,999.999 m³
DN 150 ... 300	0.005 m³	9,999,999.99 m³

Typical Headloss Curve



Approval mark

Meter cpl. and exchangeable metrological module

Marking CE M-XX* 0102


DN 40 ... 150: DE-09-MI001-PTB 010

DN 200 ... 300: DE-15-MI001-PTB 014

* year of production

INDORAYA POWER ENERGI


Installation

Pipe	horizontal vertical	
Meter head	upwards sideways	

Installation requirements

- Unrestricted straight pipe upstream 0 x DN
- No abrupt restrictions directly downstream of the meter

Dimension picture



Dimensions

Nominal Diameter		DN	DN 40	DN 50	DN 65	DN 80	DN 100	DN 125	DN 150	DN 200	DN 250	DN 300
Overall length	L	mm	220	200 270 300	200 300	200 225 300 350	250 350 360	250	300 500	350	450	500
Width	B	mm	166	166	186	201	220	250	285	340	405	460
Heigh	H	mm	120	120	120	150	150	160	177	214	238	264
Height to pipe axis	h	mm	69	73	85	95	105	118	135	162	194	226
Dismantling height	g	mm	200	200	200	270	270	280	356	449	474	499

Weight PN16

Nominal Diameter		DN	40	50	50	50	65	65	80	80	80	80
Overall length	L	mm	220	200	270	300	200	300	200	225	300	350
Meter		kg	8.0	8.5	9.6	9.9	10.1	12.0	12.4	14.2	16.3	17.7
Metrological module		kg	1.5	1.5	1.5	1.5	1.5	1.5	3.2	3.2	3.2	3.2
Body		kg	6.5	7.0	8.1	8.4	8.6	10.5	9.2	11.0	13.1	14.5

Nominal Diameter		DN	100	100	100	125	150	150	200	250	300
Overall length	L	mm	250	350	360	250	300	500	350	450	500
Meter		kg	17.0	20.0	20.2	20.7	35.9	44.2	56.9	79.4	103.8
Metrological module		kg	3.2	3.2	3.2	3.2	5.9	5.9	9.6	9.6	9.6
Body		kg	13.8	16.8	17.0	17.5	30.0	38.3	47.3	69.8	94.2

Weight PN40


Nominal Diameter		DN	50	50	65	80	80	100	100	150	150
Overall length	L	mm	200	270	300	225	300	250	360	300	500
Meter		kg	9.7	10.7	13.1	17	18.6	20.4	22.9	44.6	52.9
Metrological module		kg	1.7	1.7	1.7	4	4	4	4	9.3	9.3
Body		kg	8	9	11.4	14.6	14.6	16.4	18.9	35.3	43.6

INDORAYA POWER ENERGI

Order example



MeiStream, DN 50, T50, PN16



Materials

Body	Cast iron (PN16) Ductile iron (PN40)
Metrological module	Engineering polymer
Rotor	Engineering polymer
We also use the following materials	Brass Stainless steel

© 2026 Sensus International. All trademarks, logos and brand names are the property of their respective owners. All rights reserved.

Sensus GmbH Hannover
Meineckestraße 10
30880 Laatzen, Germany

Contact:
info@sensus-int.com